

TECHNICAL SPECIFICATION



HEAD PROTECTION

EVO® VISTAshield® Micro Peak Revolution® Wheel Ratchet Non Vented

White / White / AMC170-004-F00



DESCRIPTION

EVO@VISTAshield® is a next generation feature-rich safety helmet based on the proven Evolution® head protection technology, incorporating a fully retractable optical class 1 integrated faceshield offering A-rated impact protection. The eyewear is easy to deploy, adjust and maintain, ensuring protection is on hand whenever required.

The EVO@VISTA® has been developed from the ground up to seamlessly integrate with a wide range of above the neck PPE. The helmet combines a super strong ABS shell designed for superior all day protection with the comfort benefits of the Evolution® 3D-Adjustment™ harness system.

OPTIONS

White / Smoke (AMC170-005-F00)

White / White (AMC170-004-F00)

SAFETY STANDARDS

EN 397 • EN 50365 • EN 166 • EN 170





























Veiligheidstechniek Nederland BV
Ijzerweg 67
5342 LX Oss

T. +31(0)412 - 69 55 55
E. info@vtn.nl

VEILIGHEIDSTECHNIEK
NEDERLAND

SPECIFICATIONS

| | | | |
|--|---|---|---|
|  | Peak Micro |  | Impact Resistance 50 Joules |
|  | Electrical Insulation 1000 V |  | Lateral Deformation Yes |
|  | Molten Metal Yes |  | Maximum Temperature +50°C |
|  | Minimum Temperature -40°C |  | ABS Shell Yes |
|  | Recyclable Shell |  | Textile Harness |
|  | Depth Adjustment 3D Harness |  | Wheel Ratchet Yes |
|  | Universal Accessories Slot Yes |  | Ventilation No |
|  | BSI Kitemark Yes |  | JSPCheck Yes |
|  | RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C |  | Manufacturer's Trademark JSP Dagger |
|  | LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2 |  | Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1 |
|  | High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s Maximum protection for face shields A |  | The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional T |
|  | Resistance to Surface Damage by Fine Particles (optional) K |  | Resistance to fogging (optional) N |
|  | Visor Length 13cm |  | Product Weight 521g |

FEATURES



Prescription Protection

Fully compatible with prescription eyewear, the EVO@VISTAshield® allows the individual wearer's prescription glasses to be comfortably worn underneath the integrated overspec, reducing cost and ensuring protection and vision are not compromised.



Fully Adjustable

The EVO@VISTAshield® is effortless to retract and deploy. Pivots smoothly allowing the wearer to adjust the faceshield position maximising coverage and protection.



Compatibility

EVO@VISTAshield® has been specifically designed to maximise compatibility with JSP respirators such as the Force™8 PressToCheck™ and the Sonis® helmet mounted ear defender range.



Coverage


EVO@VISTAshield® has been designed to maximise facial coverage and is compact so does not compromise wearer movement.



Veiligheidstechniek Nederland BV
Ijzerweg 67
5342 LX Oss

T. +31(0)412 – 69 55 55
E. info@vtn.nl

VEILIGHEIDSTECHNIEK
NEDERLAND



CR2 Reflectivity

CR2 is a high intensity reflective material offering, on average, 60% more reflectivity than standard reflective clothing. CR2 is optional.



Safety Cell Protection

The safety cell concept prevents ricocheting debris travelling up the eyewear and impacting the scalp. In addition the overspec cannot make contact with the scalp, preventing injury should it be forced back on to the safety cell.



Accessories

Universal attachment slots for ear defenders. Lamp brackets and ID card holders can be fitted and CR2 reflective can be applied to improve visibility in low light.



Comfort

Compact and lightweight at only 515g. A fully adjustable wheel ratchet and unique 3D adjustment secures the helmet. A 6-point terylene harness & Egyptian cotton Chamlon™ sweatband offers unrivalled comfort.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



ID Card Holder

Clear plastic ID card holder fits standard business card size identification. Simple push and slide mechanism. A lamp bracket is positioned at the top of the unit. ID card holder is optional.



Vision

Optical class 1 eyeshield offers a panoramic view with minimal distortion. Conforms to EN166.1.AT.KN, offering impact protection, even at extremes of temperature with anti-scratch and anti-mist coatings.



Tough ABS Shell

The EVO®Vista® range features an extremely robust ABS shell designed for superior protection. It features a distinctive five stripe design and the JSP Shield.



Textile Harness

A 6 point terylene cradle harness system & Egyptian cotton Chamlon™ sweatband offers unrivalled comfort.

ACCESSORIES

Deluxe Chinstrap with Chincup

EVO® Neck Cape

Sonis® Compact Helmet Mounted Ear Defenders

Sonis®1 Helmet Mounted Ear Defenders

Sonis®3 Helmet Mounted Ear Defenders

PPE Cleaning Station & Accessories

Elasticated Chinstrap

Replacement Integrated Shield for EVO® VISTASHIELD®

Sonis® Compact Hygiene Kit

Sonis®1 Hygiene Kit

Sonis®3 Hygiene Kit

LOGO

- Front
- Back

RANGE



VIDEOS

- www.youtube.com/watch?v=wG8UFDHA-b8&t=9s
- www.youtube.com/watch?v=o0Gp0XkPbTI
- www.youtube.com/watch?v=GN02TNNZyz4&t
- www.youtube.com/watch?v=i8-pUrlrl1o

DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [Declaration of Conformity \(PDF\)](#)



Veiligheidstechniek Nederland BV
 IJzerweg 67
 5342 LX Oss
 T. +31(0)412 - 69 55 55
 E. info@vtn.nl